



## Safety Data Sheet

Page 1 of 14

LOCTITE 263 BO50MLEN/CH/JP known as 263  
THREADLOCKER 50 ML A/P

SDS No. : 347828  
V001.12

Revision: 29.01.2021  
printing date: 13.09.2024

### Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:**

LOCTITE 263 BO50MLEN/CH/JP known as 263 THREADLOCKER 50 ML A/P

**Other means of identification:**

LOCTITE 263 BO50MLEN/CH/JP

**Product code:**

IDH1307415

**Recommended use of the chemical and restrictions on use**

**Intended use:**

Adhesive

**Identification of manufacturer, importer or distributor**

**Manufacturer:** Henkel Loctite (China) Co. Ltd, No. 90 Zhu Jiang Road, Yantai Economic, Technological Development Zone, 264006 Shangdong Province, China Tel: +86-535-6399803 Fax: +86-535-6371999

**Importer:** Henkel Thailand Ltd The Offices at Centralworld, 35th Floor, 999/9 Rama 1 Rd, Kwang Patumwan, Khet Patumwan, Bangkok 10330, Thailand. Phone : +6622098000 Fax : +6622098008

**E-mail address of person responsible for Safety Data Sheet:**

ap-ua-psra.sea@henkel.com

**Emergency information:**

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

### Section 2. Hazards identification

**GHS Classification:**

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 2	
Skin sensitizer	Category 1	
Specific target organ toxicity - single exposure	Category 3	respiratory tract irritation
Chronic hazards to the aquatic environment	Category 2	

**GHS label elements:**

**Hazard pictogram:**



**Signal word:**

Warning

**Hazard statement:**

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H411 Toxic to aquatic life with long lasting effects.

**Precaution:**

**Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

P302+P352 IF ON SKIN: Wash with plenty of water.  
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P391 Collect spillage.

**Storage:**

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Disposal:**

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Section 3. Composition / information on ingredients**

**Substance or Mixture:**  
Mixture

**Declaration of hazardous chemical:**

Hazard component CAS-No.	Content	GHS Classification
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	10- 30 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1B H317 Specific target organ toxicity - single exposure 3 H335 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	1- 10 %	Skin sensitizer 1B H317 Acute hazards to the aquatic environment 3 H402
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	1- 10 %	Flammable liquids 4 H227 Organic peroxides E H242 Acute toxicity 4; Oral H302 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1 H314 Specific target organ toxicity - repeated exposure 2 H373 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
maleic acid 110-16-7	0.1- 1 %	Acute toxicity 4; Oral H302 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Specific target organ toxicity - single exposure 3 H335 Acute hazards to the aquatic environment 3 H402
Acetic acid, 2-phenylhydrazide 114-83-0	0.1- 1 %	Acute toxicity 3; Oral H301 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Carcinogenicity 2 H351
1,4-Naphthalenedione 130-15-4	< 0.1 %	Acute toxicity 3; Oral H301 Acute toxicity 1; Inhalation H330 Skin corrosion/irritation 2; Dermal H315 Serious eye damage/eye irritation 2A

		H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
--	--	---

**Section 4. First aid measures**

**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.  
Seek medical advice.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

**Ingestion:**

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.  
Seek medical advice.

**Indication of immediate medical attention and special treatment needed:**

See section: Description of first aid measures

**Section 5. Fire fighting measures**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Combustion behaviour:**

Non flammable product (flash point is greater than 100°C (CC))

**Special protection equipment and precautions for firefighters:**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Hazardous combustion products:**

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**Additional fire fighting advice:**

In case of fire, keep containers cool with water spray.

**Section 6. Accidental release measures**

**Personal precautions:**

Avoid skin and eye contact.  
Ensure adequate ventilation.  
Wear protective equipment.  
See advice in section 8

**Environmental precautions:**

Do not empty into drains / surface water / ground water.

**Clean-up methods:**

For small spills wipe up with paper towel and place in container for disposal.  
For large spills absorb onto inert absorbent material and place in sealed container for disposal.  
Dispose of contaminated material as waste according to Section 13.

## Section 7. Handling and storage

### Handling:

Avoid skin and eye contact.  
See advice in section 8

### Storage:

Ensure good ventilation/extraction.  
Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.  
Refer to Technical Data Sheet

## Section 8. Exposure controls / personal protection

### Components with specific control parameters for workplace:

#### Respiratory protection:

Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)

#### Hand protection:

Chemical-resistant protective gloves (EN 374).  
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):  
nitrile rubber (NBR;  $\geq 0.4$  mm thickness)  
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):  
nitrile rubber (NBR;  $\geq 0.4$  mm thickness)  
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Wear protective glasses.  
Protective eye equipment should conform to EN166.

#### Body protection:

Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

#### Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

#### Hygienic measures:

Take off contaminated clothing and wash before reuse.  
Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.

## Section 9. Physical and chemical properties

<b>Appearance:</b>	red liquid
<b>Odor:</b>	characteristic
<b>Odor threshold (CA):</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point / freezing point:</b>	No data available.
<b>Specific gravity:</b>	No data available.
<b>Boiling point:</b>	No data available.
<b>Flash point:</b>	100 °C (212 °F) Estimated
<b>Evaporation rate:</b>	No data available.
<b>Flammability (solid, gas):</b>	No data available.
<b>Lower explosive limit:</b>	No data available.
<b>Upper explosive limit:</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Density:</b>	No data available.
<b>Solubility:</b>	No data available.
<b>Partition coefficient: n-octanol/water:</b>	No data available.
<b>Auto ignition:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.
<b>VOC content:</b> (2010/75/EC)	< 3 %

## Section 10. Stability and reactivity

**Reactivity/Incompatible materials:**  
Peroxides.

**Chemical stability:**  
Stable under recommended storage conditions.

**Conditions to avoid:**  
Stable under normal conditions of storage and use.

**Hazardous decomposition products:**  
carbon oxides.

## Section 11. Toxicological information

**Oral toxicity:** Acute toxicity estimate (ATE) : > 2,000 mg/kg  
Method: Calculation method

**Inhalative toxicity:** Acute toxicity estimate (ATE) : > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: Vapor.  
Method: Calculation method

**Dermal toxicity:** Acute toxicity estimate (ATE) : > 2,000 mg/kg  
Method: Calculation method

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.  
SKIN: Redness, inflammation.  
SKIN: Rash, Urticaria.  
RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

**Acute oral toxicity:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	LD0
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	LD50
	Value	10,837 mg/kg
	Species	rat
	Method	not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LD50
	Value	382 mg/kg
	Species	rat
	Method	other guideline:
maleic acid 110-16-7	Value type	LD50
	Value	708 mg/kg
	Species	rat
	Method	not specified
Acetic acid, 2-phenylhydrazide 114-83-0	Value type	LD50
	Value	270 mg/kg
	Species	rat
	Method	not specified
1,4-Naphthalenedione 130-15-4	Value type	LD50
	Value	190 mg/kg
	Species	rat
	Method	not specified

**Acute dermal toxicity:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	LD0
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	mouse
	Method	not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LD50
	Value	530 - 1,060 mg/kg
	Species	rat
	Method	other guideline:
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	Acute toxicity estimate (ATE)
	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
maleic acid 110-16-7	Value type	LD50
	Value	1,560 mg/kg
	Species	rabbit
	Method	not specified

**Skin corrosion/irritation:**

2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	Draize Test
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	Draize Test
maleic acid 110-16-7	Result	irritating
	Exposure time	24 h
	Species	human
	Method	Patch Test

**Serious eye damage/irritation:**

2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
maleic acid 110-16-7	Result	highly irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)



**Respiratory or skin sensitization:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	negative
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Result	negative
	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
Method	not specified	
maleic acid 110-16-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	no data
	Method	Ames Test
maleic acid 110-16-7	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**Repeated dose toxicity:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	daily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Result	
	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
maleic acid 110-16-7	Result	NOAEL= $\geq$ 40 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Section 12. Ecological information**

**General ecological information:** Do not empty into drains / surface water / ground water.

**Ecotoxicity:** Toxic to aquatic life with long lasting effects.

**Toxicity:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	LC50
	Value	1.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	EC50
	Value	14.43 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Value type	EC10
	Value	0.43 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	LC50
	Value	16.4 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	18.6 mg/l
	Acute Toxicity Study	Algae

	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LC50
	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC50
	Value	18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	ErC50
	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC10
	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	not specified
maleic acid 110-16-7	Value type	LC50
	Value	> 245 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus
	Method	DIN 38412-15
maleic acid 110-16-7	Value type	EC50
	Value	42.81 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
maleic acid 110-16-7	Value type	EC50
	Value	74.35 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	11.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	Value type	EC10
	Value	44.6 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	18 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
1,4-Naphthalenedione 130-15-4	Value type	EC50
	Value	0.011 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Dunaliella bioculata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Persistence and degradability:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	16.8 %

	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	85 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Result	
	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
maleic acid 110-16-7	Result	readily biodegradable
	Route of application	aerobic
	Degradability	97.08 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4	Result	not readily biodegradable.
	Route of application	no data
	Degradability	0 - 60 %
	Method	OECD 301 A - F

**Bioaccumulative potential / Mobility in soil:**

3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LogPow	5.25
	Temperature	20 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LogPow	2.3
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	Bioconcentration factor (BCF)	9.1
	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide 80-15-9	LogPow	2.16
	Temperature	
	Method	not specified
maleic acid 110-16-7	LogPow	-1.3
	Temperature	20 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Acetic acid, 2-phenylhydrazide 114-83-0	LogPow	0.74
	Temperature	
	Method	not specified
1,4-Naphthalenedione 130-15-4	LogPow	1.71
	Temperature	
	Method	not specified

**Section 13. Disposal considerations****Product****Method of disposal:**

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

**Packaging****Disposal of uncleaned packages:**

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

**Section 14. Transport information**

**Road transport ADR:**

Class: 9  
Packing group: III  
Classification code: M6  
Hazard ident. number: 90  
UN no.: 3082  
Label: 9  
Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (3,3,5-Trimethylcyclohexyl methacrylate)

**Railroad transport RID:**

Class: 9  
Packing group: III  
Classification code: M6  
Hazard ident. number: 90  
UN no.: 3082  
Label: 9  
Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (3,3,5-Trimethylcyclohexyl methacrylate)

**Inland water transport ADN:**

Class: 9  
Packing group: III  
Classification code: M6  
Hazard ident. number: 90  
UN no.: 3082  
Label: 9  
Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (3,3,5-Trimethylcyclohexyl methacrylate)

**Marine transport IMDG:**

Class: 9  
Packing group: III  
UN no.: 3082  
Label: 9  
EmS: F-A ,S-F  
Seawater pollutant: Marine pollutant  
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (3,3,5-Trimethylcyclohexyl methacrylate)

**Air transport IATA:**

Class: 9  
Packing group: III  
Packaging instructions (passenger): 964  
Packaging instructions (cargo): 964  
UN no.: 3082  
Label: 9  
Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (3,3,5-  
Trimethylcyclohexyl methacrylate)

**Further information for transport:**

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

### Section 15. Regulatory information

**Regulatory Information:**

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

**Global inventory status:**

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ISHL (JP)	yes
IECSC	yes
NZIOC	yes
TCSI	yes
CH INV	yes
EINECS	yes

### Section 16. Other information

**Disclaimer:**

This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative.

We recommend to use a non-personal email address (e.g. SDS@your\_company.com).