



Safety Data Sheet

Page 1 of 6

LOCTITE 2700

SDS No. : 673005

V001.3

Revision: 15.12.2020

printing date: 13.09.2024

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:

LOCTITE 2700

Other means of identification:

LOCTITE 2700 BO50ML EGFD

Product code:

IDH1948763

Recommended use of the chemical and restrictions on use

Intended use:

Adhesive

Identification of manufacturer, importer or distributor

Manufacturer: Henkel Ireland Ltd., Dublin / Tallaght (Manufacturing & Research), Tallaght Business Park Whitestown, Tallaght, Dublin 24, Ireland. Phone: 00 353 1 404 6444 Fax: 00 353 1 459 9298

Importer: Henkel Thailand Ltd The Offices at Centralworld, 35th Floor, 999/9 Rama 1 Rd, Kwang Patumwan, Khet Patumwan, Bangkok 10330, Thailand. Phone : + 6622098000 Fax : +6622098008

E-mail address of person responsible for Safety Data Sheet:

ap-ua-psra.sea@henkel.com

Emergency information:

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

GHS label elements:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

Section 3. Composition / information on ingredients

Substance or Mixture:

Mixture

Declaration of hazardous chemical:

Does not contain ingredients or impurities which contribute to hazard classification.

Section 4. First aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Improper extinguishing media:

High pressure waterjet

Specific hazards arising from the chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice:

In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Wear protective equipment.

Ensure adequate ventilation.

Remove sources of ignition.

See advice in section 8

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:

Avoid skin and eye contact.
Use only in well-ventilated areas.
See advice in section 8

Storage:

Ensure good ventilation/extraction.
Keep container tightly sealed.
Store in a cool, dry place.
Keep away from sources of ignition.
Refer to Technical Data Sheet

Section 8. Exposure controls / personal protection

Respiratory protection:

Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; ≥ 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; ≥ 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:

Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Hygienic measures:

Take off contaminated clothing and wash before reuse.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

Section 9. Physical and chemical properties

Appearance:	green liquid
Odor:	mild
Odor threshold (CA):	No data available.
pH:	Not available.
Melting point / freezing point:	No data available.
Specific gravity:	No data available.
Boiling point:	> 149 °C (> 300.2 °F)
Flash point:	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	0.13 mbar (; 50 °C (122 °F))
Vapor density:	No data available.
Density:	1.1 g/cm ³
Solubility:	Insoluble
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	350.0 - 550.0 mPa.s (Cone and plate; Instrument: Haake cone and plate, RV1, C60/1°Ti; 25 °C (77 °F); Shear gradient: 129 s ⁻¹ ; Method: ;; LCT STM 740; cone & plate viscosity)
VOC content:	< 3 % (2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible materials:

Strong oxidizing agents.

Strong bases.

Acids.

Reducing agents.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

Rapid polymerization may generate excessive heat and pressure.

Conditions to avoid:

No decomposition if stored and applied as directed.

Hazardous decomposition products:

carbon oxides.

Hydrocarbons

nitrogen oxides

Section 11. Toxicological information

Symptoms of Overexposure:

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

Section 12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Section 13. Disposal considerations

Product

Method of disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

Packaging

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

Regulatory Information:

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
IECSC	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative.

We recommend to use a non-personal email address (e.g. SDS@your_company.com).

