

AQUENCE ENV 2047 ENVAFILMknown as: Adhesin LOK 2047
September 2013**TYPE** Vinyl Emulsion Adhesive**PHYSICAL PROPERTIES**

Appearance	White liquid
Viscosity (RVF#2/20/ 27°C)	1,200 – 1,700 cPs
Solids Content	50.0 – 53.5 %
pH	4 – 6
Specific Gravity	1.05 ± 0.05
Wet Tack	Aggressive
Shelf Life	6 months at ambient temperature & unopened container

OPERATING CONDITIONS

- STIR ADHESIVE THOROUGHLY BEFORE USING
- Can be applied by direct transfer from glue wheel, or extrusion
- Ready for use as supplied. May be diluted with water if necessary
- Wet film is soluble in water and dry film in acetone/water.

SUGGEST USE

AQUENCE ENV 2047 ENVAFILM is a high quality formulated emulsion adhesive for general purpose applications especially the adhesion of difficult substrates. It features a very good adhesion and fast setting properties.

PRECAUTIONS

- Rotate stock and use oldest material first.
- Keep covered to prevent drying and contamination.
- DO NOT MIX WITH OTHER ADHESIVES.
- PROTECT FROM TEMPERATURE BELOW 6°C.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.