

**AQUENCE LA 1203**known as: Adhesin 1203  
September 2013**TYPE** Vinyl Emulsion Adhesive**PHYSICAL PROPERTIES**

<b>Appearance</b>	White liquid
<b>Viscosity</b> (LVT#3/6/ 27°C)	10,000 – 15,000 cPs
<b>Solids Content</b>	37.0 – 40.0 %
<b>pH</b>	4 – 6
<b>Specific Gravity</b>	1.05 ± 0.05
<b>Wet Tack</b>	Aggressive
<b>Shelf Life</b>	6 months at ambient temperature & unopened container

**OPERATING CONDITIONS**

- STIR ADHESIVE THOROUGHLY BEFORE USING
- Can be applied by direct transfer from glue wheel, roller, any mechanical glue spreader or brush
- Ready for use as supplied. May be diluted with water if necessary
- Wet film is soluble in water and dry film in acetone/water.

**SUGGEST USE**

AQUENCE LA 1203 is a formulated vinyl emulsion adhesive for lamination sponge to board. It features a medium viscosity, good wet tack and long open time.

**PRECAUTIONS**

- Rotate stock and use oldest material first.
- Keep covered to prevent drying and contamination.
- DO NOT MIX WITH OTHER ADHESIVES.
- PROTECT FROM TEMPERATURE BELOW 6°C.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.